


RK50-3V30J

Nimi: **Ryhmäkeskus uppo/pinta**
Ryhmäkeskus, 50A, IP20C, FE

Tyyppi: RK50-3V30J
EAN: 6410033101607
Snro: 3310160

Kuvaus: Ryhmäkeskus uppo/pinta, FE, 3 kpl 40A 4-napaista vikavirtasuojakytkintä. 30 kpl jousiliitäntäistä johdonsuojakatkaisijaa. 57-mod varatila. Ovi (3310116) lisävarusteena. Värisävy RAL9016. Saman kokoinen Data-asennuskotelo DATA800 (3310109)

Pakkaus: 1
Yksikkö: KPL



Mitat

Mitat 550x800x112
Paino 14.3 kg

Luokat

Kotelointiluokka IP20C
Suojausluokka 1

Keskukset

Vikavirtasuojakytkin 4-nap. 30 mA 3
Johdonsuojakatkaisijoita B 6 A 1
Johdonsuojakatkaisijoita B 10 A 2
Johdonsuojakatkaisijoita C 10 A 9
Johdonsuojakatkaisijoita B 16 A 6
Varatilamodulit 57
Vikavirtasuojakytkimen jälkeiset johdonsuojakatkaisijat C16 9
Vikavirtasuojakytkimen jälkeiset johdonsuojakatkaisijat C10 9

Oikosulkukestoisuus ICW ≤ 10 kA
Max. Liitäntä kaapeli ≤ 35 mm²

Värit

Väri Valkoinen
Värikoodi RAL9016

ETIM

ETIM 7 EC002288 (EC002288)
ETIM 8 EC002288 (EC002288)

RK50-3V30J

ETIM 8

Number of phases	3
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	30
Number of direct groups	12
Number of groups behind earth leakage switch	18
Number of earth leakage switches 30 mA	3
Number of poles main switch	3
Main switch rated current	63 A
With socket outlet	no
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	800 mm
Width	550 mm
Width in number of modular spacings	24
Depth	112 mm
Built-in depth	95 mm
Extension possible	yes